



H.M.I.S. RATING	
Health	1
Flammability	0
Reactivity	0
Protective Equip.	E

## Material Safety Data Sheet – OSHA 174

### Material Safety Data Sheet

May be used to comply with OSHA's Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

### US Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB No. 1218-0072

## JETCOAT Fibered Emulsion Roof and Foundation Coating

Item #: 60715  
60711

### SECTION I - Manufacturer / Product Information

<b>Manufacturer's Name:</b> JETCOAT Inc.	<b>Emergency Telephone No.:</b> Chemtrec: 1-800-424-9300
<b>Address:</b> 472 S. Brehl Avenue Columbus, OH 43223	<b>Telephone Number for Information:</b> 1-800-394-0047
	<b>Date Prepared:</b> January 21, 2008

### SECTION II - Chemical Identity Information

Ingredient	CAS #	OSHA PEL	ACGIH TLV	Other Limits	Percent
Ball Clay	1332-58-7	10 mg/m3	N/A		
Asphalt	8052-42-4	N/A	5 mg/m3		
Calcium Carbonate	1317-65-3	5 mg/m3	2mg/m3		
Cellulose	9004-34-6	15 mg/m3	10 mg/m3		

### SECTION III - Physical / Chemical Characteristics

<b>Boiling Point:</b> 100° Celsius (212° Fahrenheit)	<b>Specific Gravity (H2O = 1):</b> 1.17
<b>Vapor Pressure (mm Hg):</b> Nearly equal to water.	<b>Melting Point:</b> N/A
<b>Vapor Density (AIR = 1):</b> <1	<b>Evaporation Rate (Butyl Acetate = 1):</b> Approximately 1.8
<b>Solubility in Water:</b> Easily dispersible in the liquid state.	
<b>Appearance and Odor:</b> Black liquid, asphaltic odor.	

### SECTION IV - Fire and Explosion Hazard Data

<b>Flash Point (Method Used):</b> N/A	<b>Flammable Limits:</b> N/A	<b>LEL:</b> N/A	<b>UEL:</b> N/A
<b>Extinguishing Media:</b> Foam, CO2, dry chemical, water fog, other.			
<b>Special Fire Fighting Procedures:</b> Full protective equipment, including self-contained breathing apparatus to be worn. Water cool sealed containers in area of fire to prevent rupture due to steam generation.			
<b>Unusual Fire and Explosion Hazards:</b> N/A			

### SECTION V - Reactivity Data

<b>Stability:</b> Unstable: Stable: X	<b>Conditions to Avoid:</b> Keep from freezing and extreme heat.
<b>Incompatibility (Materials to Avoid):</b> Strong oxidizers.	
<b>Hazardous Decomposition or Byproducts:</b> Combustion may yield fumes, smoke, carbon monoxide, carbon dioxide and other toxic pyrolysis products.	
<b>Hazardous Polymerization:</b> May Occur: Will Not Occur: X	<b>Conditions to Avoid:</b> N/A

