



ROOFERS PRIDE® Flashing Cement

Professional Grade Flashing and Repair Product

- Long-Lasting Protection
- All-Weather Formula
- Will Not Run or Sag
- Added Flexibility & Elasticity
- Superior Flashing, Patching &

- Leak Repair Cement
- Meets ASTM D 4586 Type 1 and ASTM D 3409



Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A professional grade flashing and repair product that cures to a tough, protective barrier. Its non-sag property and exceptional adhesion makes this an ideal cement for the construction and repair of all flashings, metal joints, seams, coping, vent pipes, skylights and chimneys. This cold applied cement is ideally suited for sealing cracks, holes and tears in built-up roofs and modified bitumen.

Uses

- Splits & Seams
- Vents
- Metal Joints
- Coping
- Flashings
- Skylights
- Chimneys

Surface Preparation

All surfaces to be treated must be free from oil, grease and other foreign materials prior to application. The surface must be firm and free from loose material. On composition roofs, open any breaks or blisters to be patched and permit to dry out before applying this product.

Application

Trowel Grade Material. Allow at least 24 hours to dry (70 °F and less than 50% humidity with no rain) before applying a surface coating. Use above or below grade.

Drying Time

Dries to the touch in 8-24 hours, depending on weather conditions.

Clean Up

- Clean up with waterless hand cleaner immediately after use.

Weather Conditions

- Do not apply if rain is imminent within 24 hours of application.

Coverage (Approximate)

- Approximately 12 square feet per gallon.

Precautions

- Do Not Heat Or Thin
- Do Not Store Container At Temperatures Above 100 ° F
- Combustible. Contains Petroleum Distillate

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 Gm/Liter Max
- Use With Adequate Ventilation
- Keep Out Of Reach Of Children

ROOFERS PRIDE® Flashing Cement
Professional Grade Flashing and Repair Product

Form No.: JC-TD61435

Packaging

Item #	Container Size	Pack	Weight
61435	4.75 Gallon Pail	1	50 lbs.
61431	.9 Gallon Pail	6	56 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Calcium Carbonate	1317-65-3
Mineral Spirits	64742-88-7
Cellulose Fibers	9004-34-6
Attapulgate Clay	12174-11-7