



# All-Weather Roof Patch

## Water Repellent Sealing Compound

- Bonds Rapidly to Wet, Moist & Cold Surfaces
- Use On Wet or Dry Surfaces
- Seals Leaks, Even in Rain
- Manufactured to Meet the Requirements of ASTM D-4586 & D-3409



### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

A thick blend of liquid asphalt and fibers specially designed as a patching material, adhesive and general utility sealing compound that imparts water-repellency to flashings, seams, or patches in roofs and gutters. Dries black.

### Uses

- Splits & Seams
- Vents
- Metal Joints
- Coping
- Flashings
- Skylights
- Chimneys

### Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts.

### Application

**Pails:** Apply material with a mason's trowel to about 1/8" thick, smoothing down all edges. Mend large cracks, breaks, or loose seams by applying cement to defective area. Extend cement to three inches beyond area to be repaired. Spot stick Reinforcing Fabric repair material in position over entire area and apply an additional layer of cement. Leaks around vent pipes, spouts, valleys, skylights, chimneys and flashings can be made weather tight by applying JETCOAT All-Weather Roof Patch.

**Tubes:** Trim nozzle to desired bead size. Puncture foil at innerbase of nozzle. Using a caulking gun,

apply to a minimum wet thickness of 1/4"

### Drying Time

Dries to the touch in 8-24 hours, depending on weather conditions.

### Clean Up

- Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

### Weather Conditions

- Can be used in wet or dry conditions.

### Coverage (Approximate)

- Approximately 12 square feet per gallon at 1/8 inch thick.
- Approximately 3 square feet per quart at 1/8 inch thick.
- One 10 ounce tube will fill approximately 17 lineal feet at 3/8 inch thick.
- One 29 ounce tube will fill approximately 49 lineal feet at 3/8 inch bead.

### Precautions

- Do Not Heat or Thin
- Do Not Store Container at Temperatures Above 100 °F
- Do Not use Where Hydrostatic Pressures May be Encountered
- Do Not Apply Over Coal Tar Surfaces
- Combustible. Contains Petroleum Distillate

### Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 300 Gm/Liter Max

**All-Weather Roof Patch**  
Water Repellent Sealing Compound

Form No.: JC-TD61715

- Use With Adequate Ventilation
- Keep Out Of Reach Of Children

## Packaging

Item #	Container Size	Pack	Weight
61715	4.75 Gallon Pail	1	50 lbs.
61711	.9 Gallon Pail	6	60 lbs.
61714	.9 Quart Can	12	33 lbs.
61718	29 Oz. Tube	12	25 lbs.
61719	10 Oz. Tube	12	11 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Calcium Carbonate	1317-65-3
Cellulose Fibers	9004-34-6
Magnesium Carbonate	546-93-0