



8-Year Premium Driveway Resurfacer

Polymer Modified Asphalt Emulsion Based Driveway Resurfacer



- 8-Year Protection
- 8X Polymer Modification
- High Solids Formula for Good Filling & Long Term Protection
- Fast and Easy to Apply
- Dries Black

Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A polymer modified asphalt emulsion based driveway resurfacer designed to beautify, protect and renew asphalt pavement surfaces. Fortified with sand for added filling, slip resistance and durability.

Uses

- Asphalt driveways & parking areas
- All asphalt pavement must weather at least six (6) months, including one summer, before using this product.
- DO NOT use on concrete surfaces.

Surface Preparation

- All cracks and holes should be repaired with JETCOAT Elastomeric Pourable Driveway Crack Filler or JETCOAT Trowel Grade Crack Filler. Allow repaired areas to cure as directed before sealing.
- For best results, surface must be thoroughly cleaned. Remove all loose dirt and foreign material and scrub all grease and oil spots with a detergent to prevent subsequent peeling and flaking. Flush entire pavement clean with water, being sure to not leave standing water.

Application

Stir sealer to a uniform consistency and continue to stir throughout application. With pavement still damp, apply a uniform coat of sealer, being sure to avoid heavy or uneven application which may result in cracking or tracking. A second coat should

be applied after the first coat has dried "to the touch" or within 24 hours at stated coverage rate. A rubber squeegee or brush is recommended for application.

Drying Time

Allow JETCOAT Driveway Resurfacer to dry to the touch, approximately 3 to 6 hours, depending on weather conditions. Allow product to cure at least 8 to 24 hours under ideal conditions (70 °F and less than 50% humidity), testing for trafficability before opening area to regular use.

Clean Up

While wet, use soap and water.

Weather Conditions

- Do not apply when temperature is expected to drop below 50 °F or when rain is possible within the next 48 hours.

Coverage (Approximate)

- Depending on pavement porosity, coverage will vary from 250-350 sq. ft. per pail.

Precautions

- Do Not Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F



8-Year Premium Driveway Resurfacer
Polymer Modified Asphalt Emulsion Based Driveway Resurfacer

Form No.: JC-TD66545

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Packaging

Item #	Container Size	Pack	Weight
66545	4.75 Gallon Pail	1	57.5 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Hydrous Aluminum Silicate	1332-58-7
Silicon Dioxide	14808-60-7
Water	7732-18-5
Blend of Fatty Amines	Proprietary
Polymer	Proprietary